


720

PAD CEMENT



ESSENTIALS LINE

TECHNICAL DATA SHEET

March 2024
Version 1.0

RESIDENTIAL

MULTI-FAMILY

COMMERCIAL

DESCRIPTION

Taylor 720 is formulated to bond carpet padding to floors to facilitate the installation of carpet. The use of pad cement prevents pad-seam separation or pad movement during carpet installation.

APPLICATION

The usual application method consists of perforating the inner seal found under the screw cap, inverting the can, and applying 2-3 beads of adhesive directly from the container to the substrate. Spread this bead with a spreader or scrap of cardboard, carpet backing or other object. The padding may be dropped into position at any time since the cement remains pressure sensitive when dry. Carpet may be stretched immediately without waiting.

PHYSICAL PROPERTIES

Base:	Synthetic Rubber, resin blend
Appearance:	Thin amber color syrup
Odor:	Mild
Coverage:	Approximately 500 square feet per gallon.
Shelf Life:	One year in unopened container at 70° F
Flammability:	Flammable
Other Features:	Waterproof when cured. Freeze/thaw stable to 10° F (-12.22° C).
Clean up:	Clean up spills immediately. Avoid letting adhesive dry on the face of carpets. If dried, use Taylor Touchdown #9 Adhesive Remover/Stripper.

DANGER

For professional use only! Extremely flammable! Toxic! Vapors may ignite explosively. Prevent buildup of vapors. Open all windows and doors; use only cross ventilation. Keep away from heat, sparks, and open flame. DO NOT smoke. Extinguish all flames and other sources of ignition during use and until all vapors are gone. Close container after use. KEEP OUT OF REACH OF CHILDREN. Harmful or fatal if swallowed. If swallowed, DO NOT induce vomiting. Call a physician immediately. Avoid breathing vapors. Avoid prolonged or repeated contact with skin or contact with eyes.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION

For warranty information, call Technical Services at **706-712-5823**, visit us on the web at **www.tayloradhesives.com** or e-mail us at **tech@tayloradhesives.com**. Flooring manufacturer's and TAYLOR's written pre-installation and installation instructions must be strictly followed or the TAYLOR warranty will be void.

TAYLOR TECHNICAL SERVICES

706.712.5823
tech@tayloradhesives.com
3343 Dug Gap Road, Dalton, GA 30721

TAYLOR
WITH YOU EVERY STEP™

PAGE 1/1