

EDGE-LOCK

CARPET EDGE SEALING ADHESIVE

ESSENTIALS LINE



TECHNICAL DATA SHEET

June 20265
Version 2.2

RESIDENTIAL

MULTI-FAMILY

COMMERCIAL

DESCRIPTION

Edge-Lock is designed to prevent carpet edge unraveling and seal cut edges to prepare them for hot-melt and glue-down seaming. This synthetic latex blend is easy-to-use, fast drying, and has blacklight tracers to verify proper application.

APPROVED FLOORING TYPES

CARPET: Broadloom (Action-Bac, jute-back, hot-melt-backed, non-vinyl-backed patterned, polyurethane & rubber backed, unitary & unitary Action-Bac, woven-backed)

APPLICATION INSTRUCTIONS

Prepare flooring and seam according to manufacturer's instructions.

1. Apply a thin, uniform bead to the edges of the carpet backing.

- Avoid contact with the nap of the carpet.
- Avoid over application to the carpet edge.

PRECAUTIONARY NOTES:

- Restrict traffic until seam sealer is dry to the touch (does not transfer).
- DO NOT expose to water for at least 4 days.
- DO NOT expose to standing water.
- Reseal lid when not in use to protect product.

REQUIRED TOOLS AND COVERAGE

FLOORING TYPES	TOOL* (IMAGES NOT TO SCALE)	ESTIMATED COVERAGE
BOND ONLY		
CARPET: Broadloom (Action-Bac, jute-back, hot-melt-backed, non-vinyl-backed patterned, polyurethane & rubber backed, unitary & unitary Action-Bac, woven-backed)	Tip Applicator Included	-75 lf/8oz

*It is the sole responsibility of the contractor/installer to determine the proper porosity of the subfloor, apply the correct amount of adhesive for the job conditions and ensure that all instructions, procedures and practices are strictly adhered to.

TAYLOR TECHNICAL SERVICES

706.712.5823
tech@tayloradhesives.com
3343 Dug Gap Road, Dalton, GA 30721

TAYLOR
ADHESIVES
An Avery Dennison Company

*Coverage is approximate and may vary depending on porosity of substrate and the angle at which the applicator tip is held.

CLEANING INSTRUCTIONS

While product is still wet: Use a dry cloth immediately to remove any excess adhesive from the surface of the wood.

While product is still soft: Use a remover/stripper, denatured alcohol or mineral spirits. Always check compatibility on a piece of scrap flooring.

STORAGE

This product should be stored at temperatures between 50-90°F (15-32°C). PROTECT FROM FREEZING.




CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION

For warranty information, call Technical Services at **706-712-5823**, visit us on the web at **www.tayloradhesives.com** or e-mail us at **tech@tayloradhesives.com**. Flooring manufacturer's and TAYLOR's written pre-installation and installation instructions must be strictly followed or the TAYLOR warranty will be void.

TAYLOR TECHNICAL SERVICES

 706.712.5823
 tech@tayloradhesives.com
 3343 Dug Gap Road, Dalton, GA 30721

**TAYLOR**
ADHESIVES
An Avery Dennison Company

EDGE-LOCK PRODUCT INFORMATION		
PRODUCT CHARACTERISTICS	Product Classification	Carpet Edge Sealing Adhesive
	Base Chemistry	Synthetic Latex Blend
	Curing Method	Evaporation
	Appearance/Color	White (wet), clear/translucent (dry)
	Odor	Extremely low
	Consistency	N/A
	Application	Squeeze bottle
	Flammability	Non-flammable
	Freeze/Thaw	Protect from freezing
	Shelf Life [Unopened Container at 70°F]	1 year
TESTING	Moisture Control	No
	RH [ASTM F2170]	N/A
	pH	N/A
	MVER [ASTM F1869]	N/A
	Porosity [ASTM F3191]	N/A
TIME	Open Time	N/A
	Flash Time	N/A
	Working Time	5-10 min
	Cure Time	12 hrs
	Pot Life	N/A
TRAFFIC	Light Traffic	24 hrs
	Heavy Traffic	24 hrs
	Heavy Rolling Loads	N/A
ACOUSTICS*	STC	N/A
	IIC	N/A
	Delta IIC	N/A
SUSTAINABILITY	Solvents	Yes
	Isocyanates	No
	VOC Wet Applied [g/L] [SCAQMD Rule #1168]	< 10 g/L
	Bio-Based Content	No
	Post-Consumer Recycled Content	No
	Mineral Abundant Content	No
	LEED v4/4.1 Points	No
	Certifications	No
	Transparency	USGBC Member
WARRANTY**	Duration (non CFI Certified)	10-Year Performance Warranty
	Duration (CFI Certified)	Lifetime Performance Warranty
	Coverage	Product performance

*IIC (delta) and STC (delta) ranges are flooring assembly specific based on third party testing and verification in a controlled environment. For any questions or further information, please contact TAYLOR Technical at 706-712-5823.

**For warranty information, view Product Warranty Certificate.