

DESCRIPTION

Fast curing tack and transition strip adhesive.

APPROVED FLOORING TYPES

Tack strips, transition strips, stair nose, trim.

APPROVED SUBSTRATES & SURFACES

- Concrete
- Terrazzo
- Ceramic tile
- APA plywood
- OSB
- Radiant heated substrates
- Concrete backer board
- Cementitious and anhydrite screed
- Primed gypcrete

SUBSTRATE & SURFACE PREPARATION

Bonding surface must be free of contamination and bondbreakers.

APPLICATION INSTRUCTIONS

Apply a 1/4" bead of adhesive to the bonding surface. Lightly mist the substrate with clean water to accelerate the curing process. Set the tack/transition strip in place and press firmly.

REQUIRED TOOLS

- Caulking gun

CLEANING

Remove dry adhesive with scraping tool, remaining residue with mineral spirits or denatured alcohol.

STORAGE

Store unopened between 50-90°F. While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 10°F. Shelf life: 1 year.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN. For more information, refer to the SDS (safety data sheet).

WARRANTY

For warranty information, call Technical Services at **706-712-5823**, visit us on the web at **www.tayloradhesives.com** or e-mail us at **tech@tayloradhesives.com**. Flooring manufacturer's and TAYLOR's written pre-installation and installation instructions must be strictly followed or the TAYLOR warranty will be void.