

ESSENTIALS LINE

TIMBERLINE™

90% MOISTURE VAPOR BARRIER, URETHANE ADHESIVE

PRODUCT HIGHLIGHT

RESIDENTIAL

MULTI-FAMILY

LIGHT COMMERCIAL

HEAVY COMMERCIAL

Timberline is a low V.O.C., one component, moisture curing polyurethane adhesive that protects wood flooring from substrate moisture (90%) and alkalinity. Designed for easy trowel-on application over concrete or wood substrates to install materials such as solid (shorts) and engineered wood flooring, parquet flooring, recycled rubber flooring, cork flooring and bamboo flooring (not strand woven).



WHY USE

- 90% moisture protection (when properly applied)
- Attractive price point
- Permanent, waterproof bond
- Protects flooring from alkali attack
- Aggressive tack, fast-grab
- High-strength, elastomeric bond
- Non-slump formula
- Easy application
- No stirring/mixing required
- Low VOC, low odor

COVERAGE: 20-180 ft²/gal
AVAILABLE IN: 4 gal
SHELF LIFE: 1 year



SCAN HERE
FOR PRODUCT
INFORMATION



USGBC
MEMBER

MOISTURE
CONTROL



RH
90%



PH
5-14



MVER
10 LBS



OPEN
TIME
10 MIN



WORKING
TIME
45-60 MIN



CURE
TIME
24 HRS



LIGHT
TRAFFIC
24 HRS



HEAVY
TRAFFIC
24 HRS

800.868.4583
tayloradhesives.com

A Meridian Adhesives Group Company

TAYLOR
WITH YOU EVERY STEP™