

### APPLICATION INSTRUCTIONS

Apply glue in a 1/8" bead (or recommended size) according to laminate/floating floor manufacturers recommended methods for installation. Coverage is approximately 400 linear feet per 16oz bottle.

#### PRECAUTIONARY NOTES:

- Do not apply adhesive if air or flooring temperature is below 55°F (12.78°C).
- Do not allow glue to dry on the surface of the flooring.
- Wait 24 hours after installation before allowing traffic.
- Reseal lid when not in use to protect product.

### CLEANING INSTRUCTIONS

While product is still wet: use a damp cloth and water to remove immediately. While product is still soft: use an adhesive remover/stripper, denatured alcohol or mineral spirits. Always check compatibility on a piece of scrap flooring.

### PRODUCT CHARACTERISTICS

Product Classification	Acrylic Latex
Base Chemistry	Vinyl Acetate Resin Blend
Curing Method	Proprietary cross-linking
Appearance	Off White to Cream
Consistency	Smooth, medium viscosity liquid
Application	Squeeze Bottle
Flammability	Non-flammable
Freeze/Thaw	Stable to 10°F (-12°C)
Shelf Life	1 year
Open Time	0 min
Working Time	30-60 min
Cure Time	24 hrs
Light Traffic	12 hrs
Heavy Traffic	24 hrs
Solvents	None
Isocyanates	None
VOC (g/L) - SCAQMD Rule#1168	0
LEED Points	N/A
Certifications	N/A

### TIME

### TRAFFIC

### SUSTAINABILITY

### STORAGE

This product should be stored at temperatures between 50-90°F (15-32° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 10°F (-12°C).

### CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

### WARRANTY INFORMATION

For warranty information, call Bruce Flooring at 1-866-243-2726, visit us on the web at [www.bruce.com](http://www.bruce.com). Flooring manufacturer's and Bruce Flooring written pre-installation and installation instructions must be strictly followed or the Bruce Flooring warranty will be void.