

RESILIENT FLOORING ADHESIVES



RESOLUTE® UNLIMITED MOISTURE VAPOR BARRIER HARD-SET ADHESIVE



NOW FEATURING NO MOISTURE TESTING

- Simple 1-part system (modified urethane)
- Strong early grab, fast-curing formula
- · High-strength, waterproof bond
- Self-leveling technology reduces telegraphing
- LEED v4 contributing (VOC 0.1 g/L)

· 1-part system increases ease of install

LEED v4 contributing (VOC 21 g/L)



















STAYLOR INNACLE ÖÖĒ

PINNACLE® HARD-SET TRANSITIONAL PSA

- Immediate access for light traffic (PSA)
- Transitional Pressure Sensitive® adhesive
- · High-strength, waterproof bond











*Working *Dry Time Time 30-60 min









STAYLOR . DYNAMIC ÖÖÖ

DYNAMIC® FIRM-SET MODIFIED TRANSITIONAL PSA

- Immediate access for light traffic (PSA)
- ColorReady® technology improves install accuracy











*Working Time



*Light Traffic 0 min



LEED v4 contributing (VOC 11 g/L)

PSA performance with hard-set resilience

· High-strength, waterproof bond



48 hrs



VERSATILE® soft-set fully repositionable psa

- Immediate access for light traffic (PSA)
- · Aggressive tack, fast-grab formula
- High-strength, water-resistant bond
- · Remains pressure sensitive
- LEED v4 contributing (VOC 11 g/L)















24 hrs







48 hrs



STEADFAST® SOFT-SET CLEAR THIN SPREAD PSA

- Immediate access for light traffic (PSA)
- · Aggressive tack, fast-grab formula
- High-strength, water-resistant bond
- Extended working time (24 hrs)
- LEED v4 contributing (VOC 12 g/L)















0 min





