

SPECIFICATION SHEET

DESCRIPTION: FLOATING FLOOR TONGUE & GROVE ADHESIVE

Taylor 2049 Tongue & Groove Flooring Adhesive is a premium adhesive that passes the stringent ANSI Type II water resistance test. It is a stable, self-cross linking emulsion which is best suited for edge gluing of all types of laminate, engineered and floating floors, even over radiant heat systems.

INSTRUCTIONS

1. Apply glue (1/8 inch bead or recommended size by flooring manufacturer) according to laminate/floating floor manufacturers recommended methods for installation
2. Allow adhesive to dry 24 hrs before subjecting to traffic.
3. Do not allow glue to dry on flooring surface.
4. Do not apply if air temperature or flooring temperature is below 55°F.

COVERAGE

Approximately 400 linear feet per 16 oz bottle.

CLEAN UP AND STORAGE

Immediately wipe off any excessive adhesive that comes to the surface with a clean cloth slightly dampened with water.

Can be stored in factory sealed containers for 1 year at 77°F.

PHYSICAL PROPERTIES

VOCs: Negligible grams per liter (calculated)
Base: Polyvinyl Acetate Emulsion
Color: Off white
Consistency: Liquid
Open Time: Approximately 1 hour
Shelf life: One year in unopened container at 70°F (21°C).

CAUTION

Causes irritation of eyes and skin on prolonged or repeated contact. DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control.